

ATLANTIC WATER TECHNOLOGY LTD

PRODUCT INFORMATION

A-193

GENERAL DESCRIPTION	A-193 is a specially selected blend of surface active agents.
USES	A-193 is a product designed to prevent foam formation and carry-over in boilers and evaporators.
COMPATIBILITY	A-193 is compatible with all metals used in boilers and evaporators and associated plant, and with other Atlantic Water Technology boiler and evaporator treatments at in-use concentrations.
APPLICATION DATA	<p>The concentration of A-193 and the frequency of application will be determined by the water quality and operating conditions.</p> <p>Dosage levels of 1.8 – 2.4 ppm are usually sufficiently effective.</p> <p>When continuous or frequent/intermittent dosing is required, it is recommended that A-193 should be diluted 7 times with clean cold water for convenient application. The product when diluted forms an opaque emulsion.</p>
TECHNICAL DATA	<p>Appearance : Very light brown liquid.</p> <p>Specific Gravity : 1.0</p> <p>pH as supplied : 7.3 approximately</p> <p>Flash point : non-flammable</p> <p>Packaging : 25 and 200 litre containers</p> <p>Transportation : non-hazardous</p>

ATLANTIC WATER TECHNOLOGY LTD

HEALTH AND SAFETY INFORMATION

A-193

POTENTIAL HAZARDS	Should cause no adverse effect under normal circumstances.
HANDLING & STORAGE	Avoid extremes of temperature. Replace cap securely after use. Recommended storage limit – 2 years.
PROTECTIVE EQUIPMENT	Wear gloves and eye/face protection in accordance with good safety practice.
SPILL PROCEDURES	Flush to drain with plenty water. Observe local disposal regulations.
FIRST AID	EYES: Rinse immediately with plenty of water. And seek medical advice. SKIN: Rinse immediately with plenty of water. INGESTION: Wash out mouth with plenty of water.
OTHER INFORMATION	A-193 is classified as non-hazardous.