

ATLANTIC WATER TECHNOLOGY LTD

PRODUCT INFORMATION

A-202

GENERAL DESCRIPTION	A-202 is a specially selected blend of tannins designed to give corrosion protection and sludge mobilization in steam boilers. A-202 exhibits oxygen scavenging properties and will form a protective mono-molecular film which inhibits corrosion of metal surfaces.
USES	A-202 is suitable for low pressure steam boilers and medium pressure boilers up to 600 psi.
COMPATIBILITY	A-202 is compatible with materials used in feed tanks, feed lines and boilers and with other Atlantic Water Technology boiler water products at in-use concentrations.
APPLICATION DATA	A-202 a residual of 120-160 ppm of tannin within the boiler water. It may be dosed to the feed tank, delivery lines or directly to the boiler shell. The point of delivery will be determined by site conditions and the arrangement of boilers to be treated.
TECHNICAL DATA	Appearance : dark brown liquid Specific Gravity : 1.1 approximately pH as supplied : 4.5 Flash point : non-flammable, non volatile Packaging : 25 and 200 litre containers Transportation : non-hazardous

ATLANTIC WATER TECHNOLOGY LTD

HEALTH AND SAFETY INFORMATION

A-202

POTENTIAL HAZARDS	May be irritating if splashed in eyes.
HANDLING & STORAGE	Avoid eye contact. Avoid extremes of temperature. Replace lid securely after use. Recommended storage limit – 2 years.
PROTECTIVE EQUIPMENT	Wear gloves and eye/face protection.
SPILL PROCEDURES	Flush to drain with copious quantity of water. Observe local effluent regulations.
FIRST AID	EYES: Rinse immediately with plenty of water for at least 10 minutes. If irritation persists seek medical advice. SKIN: Rinse immediately with plenty of water. INGESTION: Wash out mouth with plenty of water.
OTHER INFORMATION	A-202 is classified as non-hazardous.